

## Subject Index

Volume 201 · Numbers 1, 2, and 3  
January, February, and March 2018

- 95% confidence rule, 209
- Activity calculation, 66
- Advanced Test Reactor, 191, 209, 247, 267
- Attribution methodology, 1
- Average probability of failure on demand, 180
- CANDU6, 122
  - core, 138
- Chernobyl accident, 11
- Computational phantom, 155
- Computer codes
  - ABAQUS, 286
  - ATHOS3, 23
  - CINDER90, 1
  - COREDAX-2, 122
  - HEEDS, 286
  - HELIOS, 267, 209
  - MATCH, 11
  - MCNP, 66, 267
  - MCNP5, 80, 228
  - MONTEBURNS, 80
  - MCNPX-2.7, 1
  - NUCIRC, 122
  - ORIGEN2.2, 1, 80
  - ORIGEN-S, 66
  - PDQ-7, 209
  - RELAP5, 286
  - RFSP-IST, 122, 138
  - Serpent2, 122, 247
  - STAR-CCM+, 267, 286
  - SuperMC, 155, 174
- Conversion, 247
- Conversion coefficient, 155
- Corrosion and erosion
  - phenomena, 267
- Decommissioning, 66
- Dependability practices, 180
- Electrically erasable programmable
  - read-only memory, 113
- Erbia, 122
- Experiments, 228
- FDS long counter, 174
- Fission poisoning, 80
- Fluid-structure interaction, 286
- Gamma radiation, 113
- Giant dipole resonance reaction, 41
- Heat convective coefficient, 103
- Heat transfer coefficient, 99
- Heated equivalent diameter, 99
- High-temperature oxidation, 52
- Horizontal cylinder, 103
- Hydraulic equivalent diameter, 99
- Hydraulic testing, 286
- Jet emission, 11
- Laser-Compton scattering, 41
- Least-squares adjustment, 209
- Long counter, 174
- Low-enrichment uranium, 247
- Maximum likelihood, 1
- MCNP reactor criticality, 80
- Measurement data, 138
- Meteorological dispersion, 11
- Monte Carlo, 155
- Natural convection, 103
- Neutron fluence, 174
- Normal work rate, 23
- Nuclear forensics, 1
- Nuclear fuels characterization, 286
- Nuclear power plant, 180
  - commercial, 66
- Oxidation kinetics, 52
- PCR evaluation, 138
- Photonuclear transmutation, 41
- Physics, 228
- Physiological, 165
- Reactivity transient response, 80
- Recovered uranium, 122
- Research reactors, 228
- Simulations
  - thermodynamic, kinetic, neutronic, and thermohydraulic, 267
- Turbulence excitation
  - amplitude of, 23
- Wear coefficient, in situ, 23
- Wearable sensors, 165
- Wireless sensor network, 113
- Workload estimation, 165
- Zr-1%Nb fuel cladding, 52