

Liquid Fuel Performance Characterization

Here's to You, Dr. Weinberg




Dan Moneghan, PhD
Senior Technical Leader

30 January 2026
RP3C Community of Practice

Historical Work

(circa 2022)

Low-effort AI “art”
added by me




Acknowledgements

or, who did all the hard work



- Steve Krahn, Allen Croff, Irfan Ibrahim, Megan Harkema – Vanderbilt University
- N. Prasad Kadambi – Kadambi Engineering Consultants
- Brandon Chisholm – Southern Company
- Kevin Kelly, Rodolfo Vaghetto – EPRI

Qualification vs Characterization



Identifying Requirements

Requirements come from a stakeholder, such as the regulator. These are then derived into more detailed and actionable requirements by the design organization.



Developing the Hierarchy Structure

Stakeholder Requirements

▪ Level 1: Regulator Mission Statement


ASN 	ONR 	NRC 
<ul style="list-style-type: none">▪ Ensure a high level of protection for workers, patients, the public and the environment...	<ul style="list-style-type: none">▪ The public, workers and the environment shall be protected from the harmful effects of ionising radiation...	<ul style="list-style-type: none">▪ Reasonable assurance of adequate protection of public health and safety

▪ Level 2: Fundamental Safety Functions

<ul style="list-style-type: none">– Reactivity control– Containment of radioactive substances– Cooling of nuclear fuel	<ul style="list-style-type: none">– Control of reactivity– Confinement of radioactive material– Removal of heat from the core	<ul style="list-style-type: none">– Control reactivity– Limit release of radioactivity– Remove heat
--	---	---

The System Being Evaluated

Primary Fuel Salt Flow Path ■




Developing the Hierarchy Structure

Derived Requirements

- **Level 3:** Identification of Interfacing Systems
 - *What systems are needed to support the fundamental safety function?*
 - *i.e. Heat removal is supported by fuel flowing through the reactor vessel*
- **Level 4:** Identification of Functional Requirement
 - *What must take place within the system to achieve the objective?*
 - *i.e. Reactor vessel interfaces must facilitate convective heat transfer*
- **Level 5:** Mechanistic Objectives
 - *What physics are at play in the system achieving the objective?*
 - *i.e. Convective heat transfer in the reactor vessels is partially determined by the flow regime, calculated using the Reynold's number*
- **Level 6:** Fuel Properties
 - *What properties of the fuel interact with the physics under consideration?*
 - *i.e. the Reynold's number is dependent on density and dynamic viscosity*


Branch of the Hierarchy – Visualized



Objectives Hierarchy Branch for the MSRE

Regulator Mission Statement (N=1)	FSFs (N=2)	Interface Identification (N=3)	Functional Requirement Identification (N=4)	Mechanistic Objectives (N=5)	Fuel Properties (N=6)	Intrinsic or Extrinsic	Governing Equation
Provide Reasonable Assurance of Adequate Public Health and Safety	Remove Heat	Flow Through the Reactor Vessel and Internal Components	Enable Convection Heat Transfer in Fuel Inlet Piping Line 102	Facilitate Necessary Flow Regime Conditions in Fuel Inlet Piping Line 102	Fuel Salt Density	Intrinsic	$Re=(\rho vD)/\mu$
					Fuel Salt Dynamic Viscosity	Intrinsic	
				Facilitate Necessary Pressure Drop Conditions in Fuel Inlet Piping Line 102	Friction Factor	Extrinsic	$\Delta P=f(L/D)(\rho v^2)/2$
					Fuel Salt Density	Intrinsic	
				Facilitate Necessary Surface Conditions in Fuel Inlet Piping Line 102	Fuel Chemical Composition	Extrinsic	-
					Particulate Content	Extrinsic	-
				Facilitate Necessary Diffusivity Conditions in Fuel Inlet Piping Line 102	Redox Potential	Intrinsic	-
					Fuel Chemical Composition	Extrinsic	-
					Fuel Salt Specific Heat Capacity	Intrinsic	$Pr=(C_p\mu)/k$
					Fuel Salt Thermal Conductivity	Intrinsic	
				Fuel Salt Dynamic Viscosity	Intrinsic		
				Fuel Chemical Composition	Extrinsic	-	

Inlet Piping Line 102 is the pipe segment between the heat exchanger and the core




**Properties showed up multiple times.
How do I get a single envelope value?**

Calculus*

$$S(f, u) = \frac{u}{f} \left(\frac{\partial f}{\partial u} \right)_u$$


“S, is conveniently defined as the dimensionless fractional variation of the observed system response, f(u), resulting from a given fractional variation of a selected input, u”




*Hand calculation results in limited accuracy due to the tightly coupled multiphysics interactions not captured with analytical methods.

Or GOTHIC

Sensitivity of Power



Sensitivity of Primary Heat Rate to Thermophysical Properties



Evaluate each safety function's objectives against the properties that contribute to determine how values become bounding on different timescales. Build the envelope around your limiting combinations.

Measurement Uncertainty

Ok... properties identified and bounded. Now what happens?

- Measure them precisely
- MSRE operated safely and successfully with modest uncertainties

“For most cases, the uncertainty represents considerably more than either “goodness of fit” of an interpolation or internal consistency available from thermodynamics. Instead, the uncertainty may be considered as the largest probable combination of systematic and random errors associated with the value given for the property.”
(Cantor, 1968)


- Optimize your margins by valuing uncertainty reduction vs cost

Table 9-3. Measured fuel properties from ORNL-TM-2316


Fuel Property	Sources of Data/Estimation Methods	Postulated Uncertainty
Viscosity	Estimated empirically from experimental data.	25%
Thermal Conductivity	Analytical expression	>25%
Electrical Conductivity	Estimated empirically from experimental data.	20%
Phase Transition Behavior	Estimated from phase equilibria studies.	Varied with fuel salt analyzed
Heat Capacity	Analytical expression	Liquid: 4% Solid: 10%
Heat of Fusion	Analytical expression	15%
Density	Analytical expression	3%
Expansivity	Analytical expression	25%
Compressibility	Analytical expression	Not provided
Vapor Pressure	Analytical expression	“A factor of fifty from 500-700 C”
Surface Tension	Analytical expression	10-30%

Applying the Method

- Useful insights are not limited to the licensing phase of a project
- This method assists throughout design maturation
 - Replace Level 1 with any Mission Statement
 - Decompose into discrete enabling functions
 - Follow the process and develop the insights



So... Is my fuel qualified for use?



- I don't know, we have to gain acceptance of the method first!
- Appropriate sensitivity studies and uncertainty measurement help define your margins
- If you operate within the bounding polyhedron governing your properties, your fuel is, at least, satisfying the safety functions

A blue-tinted photograph of four people, two men and two women, standing in a row. They are dressed in professional attire, including lab coats and a hard hat. The text 'Together...Shaping the Future of Energy®' is overlaid in white on the image.

Together...Shaping the Future of Energy®