

ERRATUM

ANSI/ANS-8.1-1998 (R2007)

Nuclear Criticality Safety in Operations with Fissionable Materials Outside Reactors

A typographical error was identified in the heading of the first data column in Table 5 on page 7. The column heading should be $^{233}\text{UO}_2$ [2]; not $^{235}\text{UO}_2$ [2] as published. The corrected Table 5 is below.

Table 5
Single-Parameter Limits for Oxides Containing No More Than 1.5% Water By Weight at No More Than Half Density ^(a)

Parameter	$^{233}\text{UO}_2$ [2]	$^{233}\text{U}_3\text{O}_8$ [2]	$^{233}\text{UO}_3$ [2]	$^{235}\text{UO}_2$ [3]	$^{235}\text{U}_3\text{O}_8$ [3]	$^{235}\text{UO}_3$ [3]	$^{239}\text{PuO}_2$ [4]
Mass of fissile nuclide, kg	23.4	30.5	34.7	88	122	142	27
Mass of oxide, ^(b) kg	27.0	36.6	42.4	102	146	174	30
Cylinder diameter, cm	11.9	14.8	16.3	20.4	26.0	28.8	12.6
Slab thickness, cm	1.6	2.2	2.6	5.8	8.0	9.3	2.8

^(a) These are half the maximum bulk densities of Table 4.

^(b) These values include the mass of any associated moisture up to the limiting value of 1.5% by weight.